

**Filtration + Relief + Lubrication -- Page 1**

**394 Series Air Filter**

|                                                                                   |                         |                           |        |        |        |        |        |
|-----------------------------------------------------------------------------------|-------------------------|---------------------------|--------|--------|--------|--------|--------|
|  | Model                   | 394.21                    | 394.22 | 394.35 | 394.36 | 394.48 | 394.49 |
|                                                                                   | Bore Diameter           | 6,8                       |        | 10,15  |        | 20,25  |        |
|                                                                                   | Cup Volume              | 25                        |        | 75     |        | 200    |        |
|                                                                                   | Max. Working Pressure   | 1.6                       |        |        |        |        |        |
|                                                                                   | Environment Temp.       | 5~60℃                     |        |        |        |        |        |
|                                                                                   | Filtering Bore Diameter | Standard 50~75            |        |        |        |        |        |
|                                                                                   |                         | Optional 25~50 10~25 5~10 |        |        |        |        |        |

**395 Series Relief Valve**

|                                                                                   |                       |          |          |          |          |          |          |
|-----------------------------------------------------------------------------------|-----------------------|----------|----------|----------|----------|----------|----------|
|  | Model                 | 395.211  | 395.221  | 395.251  | 395.261  | 395.281  | 395.291  |
|                                                                                   |                       | 395.212  | 395.222  | 395.252  | 395.262  | 395.282  | 395.292  |
|                                                                                   |                       | 395.213  | 395.223  | 395.253  | 395.263  | 395.283  | 395.293  |
|                                                                                   |                       | 395.214  | 395.224  | 395.254  | 395.264  | 395.284  | 395.294  |
|                                                                                   | Bore Diameter         | 6        |          | 10       |          | 20       |          |
|                                                                                   | Adjusted Pressure     | 0.05~0.3 | 0.05~0.3 | 0.05~0.3 | 0.05~0.3 | 0.05~0.3 | 0.05~0.3 |
|                                                                                   |                       | 0.05~0.6 | 0.05~0.6 | 0.05~0.6 | 0.05~0.6 | 0.05~0.6 | 0.05~0.6 |
|                                                                                   |                       | 0.05~1.0 | 0.05~1.0 | 0.05~1.0 | 0.05~1.0 | 0.05~1.0 | 0.05~1.0 |
|                                                                                   |                       | 0.05~1.6 | 0.05~1.6 | 0.05~1.6 | 0.05~1.6 | 0.05~1.6 | 0.05~1.6 |
|                                                                                   | Max. Working Pressure | 1.6      |          |          |          |          |          |
|                                                                                   | Environment Temp.     | 5~60℃    |          |          |          |          |          |

**396 Series Oil Sprayer**

|                                                                                     |                       |        |        |        |        |        |        |
|-------------------------------------------------------------------------------------|-----------------------|--------|--------|--------|--------|--------|--------|
|  | Model                 | 396.21 | 396.22 | 396.35 | 396.36 | 396.48 | 396.49 |
|                                                                                     | Bore Diameter         | 6      |        | 10     |        | 20     |        |
|                                                                                     | Cup Volume            | 40     |        | 120    |        | 300    |        |
|                                                                                     | Max. Working Pressure | 1.6    |        |        |        |        |        |
|                                                                                     | Environment Temp.     | 5~60℃  |        |        |        |        |        |

**397 Series Filtering Relief Valve**

|                                                                                     |                         |                                              |          |          |          |          |          |
|-------------------------------------------------------------------------------------|-------------------------|----------------------------------------------|----------|----------|----------|----------|----------|
|  | Model                   | 397.211                                      | 397.221  | 397.251  | 397.261  | 397.281  | 397.291  |
|                                                                                     |                         | 397.212                                      | 397.222  | 397.252  | 397.262  | 397.282  | 397.292  |
|                                                                                     |                         | 397.213                                      | 397.223  | 397.253  | 397.263  | 397.283  | 397.293  |
|                                                                                     |                         | 397.214                                      | 397.224  | 397.254  | 397.264  | 397.284  | 397.294  |
|                                                                                     | Bore Diameter           | 6                                            |          | 10       |          | 20       |          |
|                                                                                     | Adjusted Pressure       | 0.05~0.3                                     | 0.05~0.3 | 0.05~0.3 | 0.05~0.3 | 0.05~0.3 | 0.05~0.3 |
|                                                                                     |                         | 0.05~0.6                                     | 0.05~0.6 | 0.05~0.6 | 0.05~0.6 | 0.05~0.6 | 0.05~0.6 |
|                                                                                     |                         | 0.05~1.0                                     | 0.05~1.0 | 0.05~1.0 | 0.05~1.0 | 0.05~1.0 | 0.05~1.0 |
|                                                                                     |                         | 0.05~1.6                                     | 0.05~1.6 | 0.05~1.6 | 0.05~1.6 | 0.05~1.6 | 0.05~1.6 |
|                                                                                     | Max. Working Pressure   | 1.6                                          |          |          |          |          |          |
|                                                                                     | Environment Temp.       | 5~60℃                                        |          |          |          |          |          |
|                                                                                     | Filtering Bore Diameter | Standard: 50~75 Optional: 25~50, 10~25, 5~10 |          |          |          |          |          |

**Filtration + Relief + Lubrication -- Page 2**

**398 Series Three(Air Filter + Relief Valve + Oil Sprayer)**

|  | Model                   | 398.213                                         | 398.223 | 398.253 | 398.263 | 398.283 | 398.293 |
|-----------------------------------------------------------------------------------|-------------------------|-------------------------------------------------|---------|---------|---------|---------|---------|
|                                                                                   | Bore Diameter           | 6                                               |         | 10      |         | 20      |         |
|                                                                                   | Cup Volume              | 0.05~1.0                                        |         |         |         |         |         |
|                                                                                   | Max. Working Pressure   | 1.6                                             |         |         |         |         |         |
|                                                                                   | Environment Temp.       | 5~60℃                                           |         |         |         |         |         |
|                                                                                   | Filtering Bore Diameter | Standard: 50~75    Optional: 25~50, 10~25, 5~10 |         |         |         |         |         |
|                                                                                   |                         |                                                 |         |         |         |         |         |

**399 Series Triad Unit(Filtering Relief Valve + Oil Sprayer)**

|  | Model                   | 399.213                                         | 399.223 | 399.253 | 399.263 | 399.283 | 399.293 |
|------------------------------------------------------------------------------------|-------------------------|-------------------------------------------------|---------|---------|---------|---------|---------|
|                                                                                    | Bore Diameter           | 6                                               |         | 10      |         | 20      |         |
|                                                                                    | Cup Volume              | 0.05~1.0                                        |         |         |         |         |         |
|                                                                                    | Max. Working Pressure   | 1.6                                             |         |         |         |         |         |
|                                                                                    | Environment Temp.       | 5~60℃                                           |         |         |         |         |         |
|                                                                                    | Filtering Bore Diameter | Standard: 50~75    Optional: 25~50, 10~25, 5~10 |         |         |         |         |         |