


JDB-2 is based on bronze **CuSn6An6Pb3** and evenly embedded with a solid under low load, high temperature and middle speed, e.g. gemel in furnace gate, convey way of the baking furnace, light industry and tooling machine industry.

Material Structure and Composition



Physical Characteristic


Load Capacity	Hardness	Friction Coef (μ)	Temperature max	PV Limit	Speed Limit
60N/mm ²	HB80~100	<0.15	-40~300℃	1.65N/mm ²	2m/s

Mechanical Properties

Density g/cm ³	Expansion Coefficient X10 ⁻⁵ /℃	Impact tenacity >KJ/m ³	Heat conduction Coefficient W (m*k)	Elongation >%	Pressure Resistant Strength >N/mm ²	Elasticity Coefficient KN/mm ²
8.2	1.6~2.0	300~400	38~55	12	755	100~140

Specification Size


Cylinder Series Specification



d	D	IDF7	ODp7		L															
					8	10	12	15	16	20	25	30	35	40	50	60	70	80		
8	12	8	+0.028	12	+0.036 +0.018	0808	0810	0812	0815											
10	14	10	+0.013	14		1008	1010	1012	1015		1020									
12	18	12	+0.034 +0.016	18			1210	1212	1215	1216	1220	1225	1230							
13	19	13		19		1310		1315	1316											
14	20	14		20	+0.043 +0.022		1410	1412	1415		1420	1425	1430							
15	21	15		21			1510	1512	1515	1516	1520	1525	1530							
16	22	16		22			1610	1612	1615	1616	1620	1625	1630	1635	1640					
18	24	18		24				1812	1815	1816	1820	1825	1830	1835	1840					
20	28	20		28			2010	2012	2015	2016	2020	2025	2030	2035	2040	2050				
22	32	22		+0.041	32	+0.051 +0.026		2212	2215		2220	2225								
25	33	25		+0.020	33			2512	2515	2516	2520	2525	2530	2535	2540	2550	2560			
30	38	30			38			3012	3015		3020	3025	3030	3035	3040	3050	3060			
35	45	35		45						3520	3525	3530	3535	3540	3550	3560				
40	50	40	+0.050	50									4030	4035	4040	4050	4060	4070	4080	
45	55	45	+0.025	55	+0.062								4530	4535	4540	4550	4560			
50	60	50		60	+0.032								5030	5035	5040	5050	5060	5070	5080	


d	D	IDF7		ODp7		L										
						30	35	40	50	60	70	80	100	120	130	140
50	62	50	+0.050	62	+0.062 +0.032	5030	505	5040	5050	5060	5070					
50	65	50	+0.025	65		5030		5040	5050	5060	5070	5080	50100			
55	70	55	+0.060 +0.030	70				5540	5550	5560	5570					
60	74	60		74		6030	6035	6040	6050	6060	6070	6080				
60	75	60		75		6030	6035	6040	6050	6060	6070	6080	60100			
63	75	63		75						6360	6370	6380				
65	80	65		80					6550	6560	6570	6580				
70	85	70		85	+0.072 +0.037		7035	7040	7050	7060	7070	7080	70100			
70	90	70		90					7050	7060	7070	7080				
75	90	75	90						7560	7570	7580	75100				
75	95	75	95						7560	7570	7580	75100				
80	96	80	96					8040	8050	8060	8070	8080	80100	80120		
80	100	80	100						8040	8050	8060	8070	8080	80100	80120	80140
90	110	90	110	+0.071 +0.036		9030			9050	9060	9070	9080	90100	90120		
100	120	100	120						10060	10070	10080	100100	100120		100140	
110	130	110	130		+0.083 +0.043						11080	110100	110120			
120	140	120	140									12080	120100	120120		120140
125	145	125	145										125100	125120		
130	150	130	150										130100		130130	
140	160	140	160										140100			140140
150	170	150	170									150100			150150	
160	180	160	180									160100			160150	

Flange Bushing Specification




d	D	ID	F7	OD	p7	F	e ₁	L											
								15	20	25	30	35	40	50	60	80	100		
10	14	10	+0.028 +0.013	14	+0.036 +0.018	22	2	1015	1020										
12	18	12	+0.041 +0.020	18	+0.043 +0.022	25	3	1215	1220										
13	19	13		19		26		1315	1320										
14	20	14		20		27		1415	1420										
15	21	15		21		28		1515	1520	1525	1530								
16	22	16		22		29		1615	1620	1625	1630								
20	28	20		30		40		2015	2020	2025	2030		2040						
25	33	25	35	45	2515	2520	2525	2530		2540									
30	38	30	40	50		3020	3025	3030	3035	3040	3050								
31.5	40	31.5	40	50		31.520			3535										
35	45	35	+0.050 +0.025	45	+0.051 +0.026	60	5	3520		3530		3540	3550						
40	50	40		50		65		4020		4030		4040	4050						
45	55	45		55		70			4530		4540	4550	4560						
50	60	50		60		75			5030		5040	5050	5060						
55	65	55		65		80					5540	5550	5560						
60	75	60		75		85		+0.062 +0.032	90	7.5				6040	6050		6080		
63	75	63	75	90					6340		6350		6380						
70	85	70	85	105					7040				7080						
75	90	75	90	110					7540		7550	7560							
80	100	80	100	120	+0.072 +0.037	120	10							8060	8080	80100			
90	110	90	110	130									9/50	9060	9080				
100	120	100	120	150										10080	100100				
120	140	120	+0.071 +0.036	140		+0.083 +0.043		170								12080	120100		

Washer Specification




Item	d	D	T	Bolt			
				D1	Dry	Size	d1
JWT-10	10.2	30	3	----	----	----	----
JWT-12	12.2	40		28	2	M3	3.5
JWT-13	13.2						
JWT-14	14.2						
JWT-15	15.2			50	35	2	M3
JWT-16	16.2						
JWT-16N		18.2	35		2	M3	3.5
JWT-18	20.2	----				----	M5
JWT-20	20.2		5		40		2
JWT-20N	25.2	----		----		----	
JWT-25	25.2				45	2	M5
JWT-25N	30.2	50		2			M5
JWT-30	35.2				60	2	M6
JWT-35	35.2	70	2	M6			
JWT-40	40.2				80	7	70
JWT-45	45.2	90	7	70			
JWT-50	50.3				100	8	75
JWT-55	55.3	110	8	85			
JWT-60	60.3				120	8	90
JWT-65	65.3	125	8	95			
JWT-70	70.3				130	10	100
JWT-75	75.3	140	10	110			
JWT-80	80.5				150	10	120
JWT-90	90.5	170	10	140			
JWT-100	100.5				190	10	160
JWT-120	120.5			175			

JSP Sliding Plate Specification



Item	W	L	A	B	C	D	E	Flat Head Screw	N0. of Holes
JSP-1875	18	75	15	45				M6	2
JSP18100		100	25	50					
JSP18125		125		75					
JSP18150		150		100					
JSP2875	28	75	15	45					
JSP28100		100	25	50					
JSP28125		125		75					
JSP28150		150		100					
JSP35100	35	100	20	60				M8	3
JSP35150		150		55	55				
JSP35200		200		55	50	55			
JSP35250		250		70	70	70			
JSP35300		300		65	65	65	65		
JSP35350		350		80	75	90	80		
JSP3875	38	75	15	45				M6	2
JSP35100		100	25	50					
JSP38125		125		75					
JSP38150		100		100					
JSP4875	48	75	15	45					
JSP48100		100	25	50					
JSP48125		125		75					
JSP48150		150		100					
JSP50100	50	100	20	60				M8	3
JSP50150		150		55	55				
JSP50200		200		55	50	55			
JSP50250		250		70	70	70	65		
JSP50300		300		65	65	65	90		
JSP50400		400		90	90	90			
JSP75150	75	150		110					
JSP75200		200		80					
JSP75250		250		105					
JSP75300		300		85	85	85			
JSP75400		400		120	120	120			
JSP75500		500		115	115	115	115		

JSL Sliding Plate Specification



Item	W	L	Bolt				Size	No.	Sketch
			a	b	c	d			
JSL20*100	20	100	60	----	----	----	M8	2	A
JSL20*150		150	55	55	----	----		3	
JSL20*200		200	55	50	55	----		4	
JSL30*100	30	100	60	----	----	----	M10	2	B
JSL30*150		150	55	55	----	----		3	
JSL30*200		200	55	50	55	----		4	
JSL30*250		250	70	70	70	----		4	
JSL45*200	45	200	55	50	55	----	M10	4	C
JSL45*250		250	70	70	70	----		4	
JSL45*300		300	65	65	65	65		5	
JSL45*350		350	80	70	75	80		5	